

Demco

Pro Series

LAWN & GARDEN SPRAYERS

60 Gallon Sprayer

Great
for parks
and estates



Trailer model

Features:

- 60 gallon tank with a sloped bottom sump for total drainage, 5" fillwell, and 1 1/4" outlet.
- Gallon and liter markings on the tank.
- Agitation is standard on all tanks.
- Special molded-in baffling in bottom of all tanks for better agitation.
- Pocket on top side of tank to hold two 1 gallon jugs or one 2 1/2 gallon jug for chemical or fresh water.
- Rugged 12 gauge formed steel skid frame.
- Adjustable drawbar hitch and axles with 18 x 9.50 flotation tires on silver rims for trailer models.
- Optional lift kit to raise tongue height 3".
- Electric continuous duty motor, diaphragm pump with Viton® valves will deliver 5 GPM. Draws 9 amps at 20 PSI.
- 3.5 HP Briggs and Stratton engine with C4101 pump delivering 6.6 GPM at 2600 RPM and 50 PSI. 150 PSI max.
- 4 HP Honda with 4 roller "Silver Cast" pump (XL4101).
- Hypro® 6 roller PTO pump (C6500D) will deliver 8 GPM at 540 RPM and 50 PSI. 150 PSI max.
- Hand gun with 15' hose.
- 80" spray boom with 2 nozzles (AN1.5), 12' spray boom with 4 nozzles and spring loaded boom breakaway or 18' boom with 6 nozzles.
- Rear mount fits category "1" three-point.
- Receiver model requires class 4 receiver hitch.
- 3-section plumbing and 3-section, 21' boom is available for 60 gallon rear mount model with PTO pump.



Skid mount model



Receiver hitch model

Demco

P.O. Box 189 • Boyden, Iowa 51234 - 0189
Phone: 1-800-543-3626 • Fax: 1-800-845-6420
View all our products on the web at: www.demco-products.com

Dealer imprint area here.

Doing Our Best to Provide You the Best