

Demco

Pro Series

110 & 150 Gallon Sprayer

Features:

- 110 or 150 gallon polyethylene tank features sump, molded sight gauge and large fillwell with a no-splash fillwell cover. 5 GPM electric and gas engine roller pump units include agitation in tank.
- Heavy duty formed steel skid frame. (W-30" x L-70")
- Electric motor, diaphragm pump with Viton® valves. Draws 9 amps @ 20 PSI (delivers 5 GPM). 35 PSI maximum pressure.
- Hypro® engine driven roller pump (C4101) delivers a max. 6.6 GPM at 2600 RPM (open flow). 150 PSI maximum pressure.
- Hypro® engine driven centrifugal pump: Straight centrifugal pump. Pump delivers 94 GPM at 30 PSI. Maximum pressure is 70 PSI.
- 18" Handgun with 15' hose (380RB).
- 12', 18', 21' and 28' boom availables.
- 21' and 28' Truss-T boom features vertical and horizontal boom breakaway with 20" nozzle spacing. 10 GPA maximum output when used with electric pump.



Demco

P.O. Box 189 • Boyden, Iowa 51234 - 0189
Phone: 1-800-543-3626 • Fax: 1-800-845-6420
View all our products on the web at: www.demco-products.com

Dealer imprint area here.

Doing Our Best to Provide You the Best