



Liquid Tender Trailer



Doing Our Best to Provide You the Best

www.demco-products.com • 1.800.543.3626



Liquid Tender Trailers

Standard Features

- 24" King pin
- Main beam sizes:
Web: 1/4" high grade 100,000 yield steel
Flange: 3/8" x 5" high grade 100,000 yield steel
Cross members: 4" x 3.2# 80,000 yield jr. I-beam on 16" centers
Side rails: 6" x 8.2# structural C channel
Rub rail: 2" x 3/8" flat steel
Beam rating: 50,000 lbs per 10 linear feet
- 4 aluminum steps with handrails
- Black plastic liquid tanks eliminated light from reaching the interior contents preventing algae and microbes growth
- 11' deck space to allow room for chemical totes
- Spring assist for trailers with ramps
- Exterior mating surfaces are caulked prior to paint to prevent rust
- 16.5" x 7" brake size, color coded
- Midship turn signals

42' Liquid Tender Trailer

Length	42' Closed Tandem Axle
Width	102"
Transition Drop	19.5" between decks
Tank Size Range	2,350 - 3,250 gallons
Frame Construction	16" I-Beam
Axle (s)	2 x 25,000 lbs. (ABS on 1 Axle)
Tires	255/70 R22.5 - 16 PLY DOT Tire & Wheel
Lights	Rubber mounted LED, DOT approved tape
Capacity	55,000 lbs
Decking	1 1/8" x 7" Apitong Flooring
GVWR	68,000
Hitch Type	24" Kingpin
Suspension	3-Leaf Heavy Duty Spring Suspension

Options

- Air ride suspension
- ABS installed on second axle
- Choice of front and rear tank sizes: 2350, 2750, 3250 gallons
- Front and rear ladder options for 3250 gallon tank only
- Aluminum rims, hub piloted (each)
- Custom paint color (red, gray, white, blue)



Black plastic liquid tanks eliminate light from reaching the interior contents preventing algae and microbes growth



Aluminum steps with handrails



Apitong Flooring



Doing Our Best to Provide You the Best

4010 320th Street • Boyden, Iowa 51234

1.800.543.3626

www.demco-products.com